



Bella Premier Series Vinyl Railing Guide Specification

This section is based on the products of RDI Railing, an Oldcastle® APG brand, Atlanta, GA 30346; (877) 265-2220; www.rdirail.com

Bella Premier Series is made from Compositcore®— a material that contains no wood or organic fibers — and provides superior resistance to moisture, mold and warping. Featuring a lightly textured, durable finish, Bella Premier Series offers a deck board adapter that creates a flat “cocktail rail.” Brackets conceal fasteners for a clean finish and multiple infill styles are available.

Oldcastle® APG, a CRH Company, is North America’s leading provider of innovative outdoor living solutions that enable customers to Live Well Outside. The manufacturer’s portfolio of premier building products inspires endless possibilities while providing enduring outdoor spaces where people can connect, reflect and recharge.

SECTION 066300 - PLASTIC RAILINGS

PART 1 - GENERAL

1.1 SECTION INCLUDES

- A. Plastic resin-based-core railings.

1.2 REFERENCES

Specifier: If retaining this optional article, edit list below to correspond to those references retained in edited specification section.

- A. References, General: Versions of the following standards current as of the date of issue of the project or required by applicable code apply to the Work of this Section.
- B. ASTM International (ASTM):
 - 1. ASTM A123/A123M - Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products.
 - 2. ASTM A307 - Carbon Steel Bolts, Studs, and Threaded Rods 60,000 psi Tensile Strength.
 - 3. ASTM A500/A500M - Cold-Formed Welded and Seamless Carbon Steel Structural Tubing in Rounds and Shapes.
 - 4. ASTM B209/B209M - Standard Specification for Aluminum and Aluminum-Alloy Sheet and Plate.
 - 5. ASTM B221M - Aluminum-Alloy Extruded Bar, Rod, Wire, Profiles, and Tube.

1.3 SUBMITTALS

- A. Product Data: Manufacturer's technical literature for each product specified.
1. Include preparation instructions and recommendations.
 2. Include storage and handling requirements and recommendations.
 3. Include manufacturer's installation instructions.

Specifier: This product is available with load calculation documentation that is individually stamped by a Professional Engineer per state. Contact RDI Railing Customer Service at (877) 265-2220 for documents that pertain to your region. Delete paragraph below if requirement for Delegated Design Submittal is retained.

4. Include load calculation documentation stamped by a Professional Engineer licensed in the jurisdiction in which Project is located.

B. Shop Drawings:

1. Include plans, elevations, sections, and details.
2. Include points of attachment and their corresponding static and dynamic loads imposed on deck and post foundations.

Specifier: Retain "Delegated Design Submittal" Paragraph and related paragraphs under "Quality Assurance" and "Performance Requirements" articles when required due to railing size or other exceptional Project requirements.

- C. Delegated Design Submittal: For railings, including analysis data signed and sealed by the qualified professional engineer responsible for their preparation.

Specifier: Retain both "Samples for Initial Selection" and "Samples for Verification" paragraphs below for two-stage Samples.

- D. Samples for Initial Selection: For each finish product and finish specified, sets of color chips representing manufacturer's full range of available colors.
- E. Samples for Verification: For each material and for each color, in manufacturer's standard size.

1.4 QUALITY ASSURANCE

A. Qualification Data:

1. Manufacturer Qualifications: Company specializing in manufacturing products specified in this Section with minimum five years documented experience.
2. Installer Qualifications: Railing manufacturer, or experienced Installer with a record of successful installations of similar type and size to that specified.

Specifier: Retain paragraph below for delegated design requirement.

- B. Professional Engineer Qualifications: Documented experience with providing delegated-design engineering services of the kind required by this Section, including documentation that engineer is licensed in the jurisdiction in which Project is located.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Transport, handle, store and protect railing components so they are in undamaged condition when installed.
- B. Store railing components in manufacturer's unopened packaging.
- C. Store railing components off the ground in a dry, protected, covered and secure area.

1.6 WARRANTY

- A. Special Warranty: On manufacturer's standard form in which manufacturer agrees to replace components which fail in materials or workmanship within specified warranty period.

Specifier: Warranty period below is for multifamily and commercial construction. RDI Railing also offers a limited lifetime warranty for single-family residential installations.

1. Warranty Period: 20 years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Structural Requirements: Engineer railings to withstand live and dead loads according to authorities having jurisdiction and information indicated within limits and under conditions indicated, without material failure or permanent deformation of structural members.

Specifier: Retain paragraph below if retaining requirement for delegated design. Custom engineering is available via authorized Bella Premier railing dealers.

- B. Delegated Design: Design railing to withstand design and operational loads.

2.2 MANUFACTURER

- A. Basis of Design: [Bella Premier Series Vinyl Railing](#) with Compositocore® resin-based core manufactured by RDI Railing; Atlanta, Georgia 30346; (877) 265-2220; www.rdirail.com.

Specifier: Retain one of the following two subparagraphs.

1. Substitutions: Not permitted.
2. Substitutions: Submit request for substitution according to Instructions to Bidders and Division 01 General Requirements.

2.3 RAILING SYSTEM

- A. Use manufacturer's standard components.
- B. System Description:
 1. Height: [36 inches] [42 inches].
 2. Length: [67-1/8 inches] [91-1/8 inches] [115-1/8 inches] [As indicated on the Drawings].
 3. Color: [Clay] [White].

C. Top Rails:

Specifier Delete top rails not used. If more than one type of top rail, indicate locations on Drawings.

1. Contour Shaped: Resin-based core with no wood or organic fibers and acrylic exterior surfaces.
2. Rail Topper, to Support Deck Board:
 - a. Basis of Design Product: RDI Railing, Aluminum Rail Topper with Premier Deck Board.

D. Bottom Rail: 2.53-inches-wide by 2.75-inches-high.

E. Infill:

Specifier: Delete infill not used. If more than one type of infill, indicate locations on Drawings.

1. Square Balusters: 1-3/8-inch square, 0.05-inch-thick extruded PVC.
 2. Turned: Injection-molded PVC compound with rectangular top and bottom portions measuring 1-3/8 by 1-3/8 inch, 0.10 thickness and with a middle portion having concentric molded turnings.
 3. Round Balusters: 3/4-inch round, 6063-T5, black powder-coated aluminum.
- F. Posts: Vertical structural posts, 2-inch-square galvanized steel tube with 3-1/4- by 3-1/4 by 3/8-inch-thick galvanized steel plate welded to post. Structural post to be stabilized inside [4-inch] [5-inch]-square PVC post sleeve.
- G. Fasteners:
1. Stainless steel fasteners to be concealed upon installation.
 2. Attachment to Wood Decking: 3/8-inch diameter A307 bolts for through bolt attachment.
 3. Attachment to Concrete: Comply with manufacturer's instructions.
- H. Accessories: Include brackets, trim rings, hardware, and all accessories required for a complete installation.

2.4 MATERIALS

- A. Plastic Material: Manufacturer's proprietary, weather-resistant, resin-based composite material with no wood or organic fibers.
- B. Aluminum: Alloy and temper recommended by aluminum producer and finisher for type of use and finish indicated, and with not less than strength and durability properties of alloy and temper designated.
1. Extruded Bar and Tube: ASTM B221, alloy 6063-T5/T52
 2. Plate and Sheet: ASTM B209/B209M, alloy 6061-T6.
- C. Polyvinyl Chloride Components: Rigid PVC homopolymer compound modified for cold weather impact retention with high levels of Titanium Dioxide pigment for long-term ultraviolet light resistance.

- D. Steel Components: ASTM A500/A500M, Grade A cold-rolled steel tubing with G-60 zinc coating on both inside and outside surfaces in accordance with ASTM A123/A123 hot-dipped electroplating process.

PART 3 - EXECUTION

3.1 INSPECTION

- A. Examine railing system substrate with Installer present. Inspect for erection tolerances and other conditions that would adversely affect installation of railing system.
 - 1. Inspect substrate that will support railing system to determine if support components are installed as indicated on approved shop drawings and are within tolerances acceptable to railing system manufacturer.
- B. Proceed with railing installation once out-of-tolerance work and other deficient conditions are corrected.

3.2 RAILING INSTALLATION

- A. General: Install railing system in accordance with approved shop drawings and manufacturer's written instructions.
- B. Support Installation: Install blocking and other supports at locations, spacings, and with fasteners recommended by manufacturer.
- C. During installation, carefully handle and store PVC components to avoid contact with abrasive surfaces. Install components in sequence as recommended by manufacturer.

3.3 CLEANING AND PROTECTION

- A. Clean finished surfaces as recommended by railing system manufacturer.
- B. Replace damaged or discolored components that cannot be restored by field repair.

END OF SECTION