



### **Finyl Line™ Vinyl Railing Guide Specification**

This section is based on the products of RDI Railing, an Oldcastle® APG brand, Atlanta, GA 30346; (877) 265-2220; [www.rdirail.com](http://www.rdirail.com).

Finyl Line low-maintenance vinyl railing, reinforced with strong aluminum, adds character to your home while providing safety and security. Easy to install and code compliant for residential (IRC) and commercial (IBC), Finyl Line is sure to meet your railing needs. Select from a traditional T-Top profile or Deck Top profile and your choice of balusters in 3 railing color options.

Oldcastle® APG, a CRH Company, is North America's leading provider of innovative outdoor living solutions that enable customers to Live Well Outside. The manufacturer's portfolio of premier building products inspires endless possibilities while providing enduring outdoor spaces where people can connect, reflect and recharge.

## SECTION 066300 - PLASTIC RAILINGS

### PART 1 - GENERAL

#### 1.1 SECTION INCLUDES

- A. Aluminum-reinforced vinyl railing system.

#### 1.2 REFERENCES

**Specifier: If retaining this optional article, edit list below to correspond to those references retained in edited specification section.**

- A. References, General: Versions of the following standards current as of the date of issue of the project or required by applicable code apply to the Work of this Section.
- B. ASTM International (ASTM):
  - 1. ASTM B221 - Aluminum-Alloy Extruded Bar, Rod, Wire, Shape and Tube.
  - 2. ASTM D638 - Test Method for Tensile Properties of Plastics.
  - 3. ASTM D648 - Test Method for Deflection Temperature of Plastics Under Flexural Load in the Edgewise Position.

#### 1.3 SUBMITTALS

- A. Product Data: Manufacturer's technical literature for each product specified.

1. Include preparation instructions and recommendations.
2. Include storage and handling requirements and recommendations.
3. Include manufacturer's installation instructions.

Specifier: This product is available with load calculation documentation that is individually stamped by a Professional Engineer per state. Contact RDI Customer Service at (877) 265-2220 for documents that pertain to your region. Delete paragraph below if requirement for Delegated Design Submittal is retained.

4. Include load calculation documentation stamped by a Professional Engineer licensed in the jurisdiction in which Project is located.

B. Shop Drawings:

1. Include plans, elevations, sections, and details.
2. Include points of attachment and their corresponding static and dynamic loads imposed on deck and post foundations.

Specifier: Retain "Delegated Design Submittal" Paragraph and related paragraphs under Quality Assurance and Performance Requirements articles when required due to railing size or other exceptional Project requirements.

- C. Delegated Design Submittal: For railings, including analysis data signed and sealed by the qualified professional engineer responsible for their preparation.

Specifier: Retain both "Samples for Initial Selection" and "Samples for Verification" paragraphs below for two-stage Samples.

- D. Samples for Initial Selection: For each finish product and finish specified, sets of color chips representing manufacturer's full range of available colors.
- E. Samples for Verification: For each material and for each color, in manufacturer's standard size.

#### 1.4 QUALITY ASSURANCE

A. Qualification Data:

1. Manufacturer Qualifications: Company specializing in manufacturing products specified in this Section with minimum five years documented experience.
2. Installer Qualifications: Railing manufacturer, or experienced Installer with a record of successful installations of similar type and size to that specified.

Specifier: Retain below for delegated design requirement.

- B. Professional Engineer Qualifications: Documented experience with providing delegated-design engineering services of the kind required by this Section, including documentation that engineer is licensed in the jurisdiction in which Project is located.

#### 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Transport, handle, store and protect railing components so they are in undamaged condition when installed.

- B. Store railing components in manufacturer's unopened packaging.
- C. Store railing components off the ground in a dry, protected, covered and secure area.

#### 1.6 WARRANTY

- A. Special Warranty: On manufacturer's standard form in which manufacturer agrees to replace components which fail in materials or workmanship within specified warranty period.

Specifier: Warranty period below is for multifamily and commercial construction. RDI also offers a limited lifetime warranty for single-family residential installations.

1. Warranty Period: 20 years from original date of purchase.

### PART 2 - PRODUCTS

#### 2.1 PERFORMANCE REQUIREMENTS

- A. Structural Requirements: Engineer railings to withstand live and dead loads according to authorities having jurisdiction and information indicated within limits and under conditions indicated, without material failure or permanent deformation of structural members.

Specifier: Retain paragraph below if retaining requirement for delegated design. Custom engineering is available via authorized Finyl Line vinyl railing dealers.

- B. Delegated Design: Design railing to withstand design and operational loads.

#### 2.2 MANUFACTURER

- A. Basis of Design: [Finyl Line™](#) Vinyl Railings manufactured by RDI Railing; Atlanta, Georgia 30346; (877) 265-2220; [www.rdirail.com](http://www.rdirail.com).

Specifier: Retain one of the following two paragraphs.

1. Substitutions: Not permitted.
2. Substitutions: Submit request for substitution according to Instructions to Bidders and Division 01 General Requirements.

#### 2.3 VINYL RAILING SYSTEM

- A. Use manufacturer's standard components.
- B. Railings:
  1. Height: [36 inches] [42 inches].
  2. Length: [48 inches] [60 inches] [72 inches] [96 inches] [120 inches] [As indicated on the Drawings].
  3. Color: [White] [Clay] [Sand].
- C. Top Rail: Reinforce with manufacturer's standard aluminum H channel conforming to shape of vinyl extrusion and running continuously through length of member

1. T-shaped with flat 2-inch center and sloping on both sides. 3-1/2 by 3-1/2-inch extruded PVC, 0.090-inch thickness.
    - a. Product: RDI Railing, T Top.
  2. T-shaped with thin top, 3-1/4 by 3-1/2 inch extruded PVC, 0.090-inch thickness.
    - a. Product: RDI Railing, Deck Top.
- D. Bottom Rail: 3-1/2 by 2 inches, extruded PVC, 0.090-inch thickness. Reinforce with manufacturer's standard aluminum T or H channel conforming to shape of vinyl extrusion and running continuously through length of member.
- E. Infill:

Specifier: Delete infill not used. If more than one type of infill, indicate locations on Drawings.

1. Square Balusters: 1-1/2 by 1-1/2-inch extruded PVC, 0.065-inch thickness.
2. Turned Balusters: Turned-shaped, injection-molded PVC compound with rectangular top and bottom portions measuring 1-1/2 by 1-1/2 inch, 0.06 thickness and with a middle portion having concentric molded turnings.
3. Round Balusters: ASTM B221, Alloy 6063-T5 3/4-inch round, powder-coated aluminum, black.
4. Decorative Infill Pre-Built Panels: Manufacturer's prefabricated infill panels in the following pattern:

Specifiers: Patterns below refer to RDI Railing proprietary patterns. See RDI Railing website to view patterns.

- a. [Chippendale][Freeport].

Specifier: Verify availability of decorative screen panel patterns and colors with [RDI Railing \(877\) 265-2220](tel:8772652220). Sanibel, Optic and River Rock are only available in Black.

5. Decorative Screen Panels: Manufacturer's prefabricated screen panels. Provide adaptor kit for attachment to framing.:
    - a. Size: 33 by 68 by 0.3 inches.
    - b. Pattern: [Boardwalk] [Sanibel] [River Rock] [Optic].
    - c. Color: [White] [Gray] [Black].
- F. Posts:
1. Sleeves: 4 by 4 inch extruded PVC.
  2. Structural Posts:
    - a. Residential: 2 by 2 inch by 0.08 inch thickness galvanized steel tube.
    - b. Commercial: 2 by 2 inch by 0.12 inch thickness galvanized steel tube.
  3. Base Plates: 3-1/4 inch by 3 1/4 inch by 3/8-inch thick galvanized steel plate welded to post. Include galvanized steel bottom sandwich plate for blocking purposes.
- G. Fasteners:

1. Stainless steel fasteners to be concealed upon installation.
2. Attachment to Wood Decking: 3/8-inch diameter A307 bolts for through bolt attachment.
3. Attachment to Concrete: Comply with manufacturer's instructions.

H. Accessories: Include brackets, snap-in bracket covers, trim rings, and all accessories required for a complete installation.

## 2.4 MATERIALS

A. Polyvinyl Chloride Components: Rigid PVC homopolymer compound modified for cold weather impact retention with high levels of Titanium Dioxide pigment for long-term ultraviolet light resistance.:

1. Tensile Modulus: ASTM D638, 425,000 psi.
2. Heat Deflection Temperature: ASTM D648, 67° c.
3. Tensile Strength: ASTM D638, 6,203 psi.
4. Thermal Expansion:  $3 \times 10^{-5}$  in/in °F.

B. Decorative Screen Panels: Manufacturer's proprietary polypropylene panels.

C. Fasteners: Stainless steel fasteners, all concealed upon installation.

## PART 3 - EXECUTION

### 3.1 INSPECTION

A. Examine railing system substrate with Installer present. Inspect for erection tolerances and other conditions that would adversely affect installation of railing system.

1. Inspect substrate that will support railing system to determine if support components are installed as indicated on approved shop drawings and are within tolerances acceptable to railing system manufacturer.

B. Proceed with railing installation once out-of-tolerance work and other deficient conditions are corrected.

### 3.2 RAILING INSTALLATION

A. General: Install railing system in accordance with approved shop drawings and manufacturer's written instructions.

B. Support Installation: Install blocking and other supports at locations, spacings, and with fasteners recommended by manufacturer.

C. During installation, carefully handle and store PVC components to avoid contact with abrasive surfaces. Install components in sequence as recommended by manufacturer.

### 3.3 CLEANING AND PROTECTION

A. Clean finished surfaces as recommended by railing system manufacturer.

B. Replace damaged or discolored components that cannot be restored by field repair.

END OF SECTION